

SAMPLE 2" x 8" MESH
(OVERLAP (1) GRID FOR WIRE TIE)



STEEL MESH IS 2"x8" SPACING
CENTRALLY LOCATED (+/- 1/2" - 0")
1" MINIMUM COVER
TOP & BOTTOM (+/- 1/2" - 0")


ALL MANHOLES BUILT PER ASTM C478
MILL CERTS AVAILABLE ON REQUEST

| MH DIA. | MESH TYPE | MESH CIRCUM. |
|---------|---------------|--------------|
| 48" | W2.1 / W1.7 | 14.5" |
| 54" | D3 / W2.1 | 15.5' |
| 60" | D3 / W2.1 | 18' |
| 72" | D3 / W2.1 | 22' |
| 84" | D4 / W2.1 | 24' |
| 96" | D4 / W2.1 | 27' |
| 108" | D4 / W2.1 | 31' |
| 120" | (2) D4 / W2.1 | 34' |
| 144" | (2) D4 / W2.1 | 41' |

ADVANTAGE PRECAST INC.

1302 Candlewood Dr N Voice: (503) 390-2048
Keizer, Oregon 97303 Fax: (503) 390-1645
<http://www.AdvantagePrecast.com>

"A Locally Owned Small Business. Where Service Comes First."



MANHOLE REINFORCING STEEL TYPE & LOCATION

Concrete: **4000psi +**
Weight:

DATE:

Jul. 2007